## **BIG BIKE PARTS**®

Copyright<sup>©</sup> 2019 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.

## **INSTALLATION INSTRUCTIONS**

PART NO. 52-947BK

LEFT SIDE BEVERAGE HOLDER

FITMENT: HONDA GOLDWING/GOLDWING TOUR DCT 2018-NEWER

4/10/2019 TOOLS NEEDED: 2MM ALLEN WRENCH

PHILLIPS SCREWDRIVER

REMOVABLE THREAD LOCK

PLEASE READ THROUGH AND UNDERSTAND THESE INSTRUCTIONS BEFORE BEGINNING.

**ESTIMATED INSTALLATION TIME: 10 TO 15 MIN.** 

## INSTALLATION:

- 1. USING PHILLIPS SCREWDRIVER, REMOVE THE TWO SCREWS ON THE FRONT OF THE LEFT HANDLEBAR CONTROL AS SHOWN IN FIG. 1. THESE WILL NOT BE REUSED.
- APPLY THREAD LOCK NEAR THE END OF THE M5 SCREWS SUPPLIED WITH THE MOUNT.
- ASSEMBLE THE M5 SCREWS AND SPACERS AS SHOWN IN FIG. 2.
- USING A PHILLIPS SCREWDRIVER, INSTALL THE SCREWS INTO THE LEFT HANDLEBAR CONTROL AS SHOWN IN FIG. 3 AND TIGHTEN. NOTE: OVER TIGHTENING CAN CAUSE DAMAGE TO THE INSERTS IN THE FRONT HALF OF THE SWITCH BLOCK.
- SLIDE THE BEVERAGE HOLDER INTO THE MOUNT AND INSTALL THE M3 SCREW AS SHOWN IN FIG. 4.
- LET THREAD LOCK CURE FOR 24 HOURS BEFORE USING CUP HOLDER.







