

INSTALLATION INSTRUCTIONS Part Number: HD-1717

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

- 1 Disconnect the breather hose from the two breather bolts. (Fig. 1)
- 2. Remove the stock air filter from the air box.
- 3. Remove the breather hose from the stock air filter. (Fig. 2)

NOTE: The K&N® air filter will utilize the OE breather hose. (Fig. 3)

- 4. Clean all the sealing surfaces in the air box.
- 5. Install the OE breather hose to the K&N® air filter. (Fig. 4)
- 6. Install the K&N® air filter into the air box.
- 7. Connect the breather hose to the two breather bolts. (Fig. 5 & 6)

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6