

INSTALLATION INSTRUCTIONS

SIGNATURE SERIES VANTAGE DASH CONSOLE BY JOHN SHOPE, CHROME

5626

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Dash Console
- 1 Bracket
- 1 M6 X 1.0 X 12MM Flat Head Socket Cap Screw


YOU WILL ALSO NEED:

Metric hex wrench set, Torx wrench set

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- STEP 2** Remove the seat.
- STEP 3** Refer to PIC 2. Unfasten the existing tank console by removing the rear mounting screw and dart clip, and loosening (not removing) the front shoulder screw located under the handlebars area. Set the rear screw aside, it will be reused. The dart clip will not be reused.
- STEP 4** Disconnect all wired components between the console and wiring harness, and remove the existing tank console from the bike. Set the console with switches aside for now.
- STEP 5** From the rear of the tank remove the tank mounting screws and washers from each side, and heat shields if applicable. Set the hardware aside, they will be reused.
- STEP 6** Refer to PIC 3. Locate provided mounting bracket and the rear screw that was removed in Step 3. Align the single mounting hole side of the bracket with the top of the tank. Lightly fasten the bracket to the tank using the existing screw.
- STEP 7** Align the two holes on the lower end of the bracket with the tank mounting holes. Fasten the bracket to tank using the screws and washers removed in Step 5, reinstall heat shields at this time if applicable. Fully tighten all bracket fasteners.
- STEP 8** Locate provided Dash Console.



KURYAKYN.COM

INSTALLATION INSTRUCTIONS


SIGNATURE SERIES VANTAGE DASH CONSOLE BY JOHN SHOPE, CHROME

5626

-CONTINUED-

STEP 9 Refer to PIC 4. Locate the existing dash console. Unfasten the switches from the existing console, being aware of the locations they were originally set, and fasten them to the new console.

If applicable, remove the power source plug from the back side of the old console. Remove the filler plug from the new console and fasten the power source plug into it.



STEP 10 Refer to PIC 5. Align the console over the tank. Connect the wired components of the console to the wiring harness on the bike.

Note: Test the reinstalled wired components to be sure they work before proceeding.



STEP 11 Refer to PIC 6. Align the front mounting hole of the dash console over the shoulder screw located on the front of the tank, located below the handlebars. Slide the mounting hole over the screw and pull the console back to set it in place.



STEP 12 Refer to PIC 7. Locate provided M6 screw. Align the rear mounting holes of the console, bracket, and tank. Insert screw and fasten to bike. Fully tighten hardware.



STEP 13 Reinstall the seat.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.





INSTALLATION INSTRUCTIONS

SIGNATURE SERIES VANTAGE DASH CONSOLE BY JOHN SHOPE, CHROME

5626

-CONTINUED-

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM

454 COUNTY ROAD VV SOMERSET, WI 54025

