



FORK OIL 10W/30

Description

Multi-grade fork oil for optimum damping at any temperature. Prevents formation of foam and protects against corrosion. A special care additive for seals prevents rapid wear and extends service life. Versatile to use for on-road and off-road purposes.

Field of application

MOTOREX FORK OIL 10W/30 is a multi-grade fork oil, which is versatile to use, meeting nearly any requirements. The flexible temperature criteria make the oil convenient to use, providing excellent results even under difficult conditions.

Advantages

- Protects against corrosion
- Prevents formation of foam
- Reduces wear
- Cares for seals

Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 300	10W/30
Colour		DIN ISO 2049	light yellow
Density at 20 °C	g/ml	ASTM D 4052	0.875
Viscosity at 40 °C	mm ² /s	DIN 51562-1	63.6
Viscosity at 100 °C	mm ² /s	DIN 51562-1	11.3
Viscosity index		DIN ISO 2909	>180
Pourpoint	°C	ASTM D 5950	<-25
Flash point	°C	DIN EN ISO 2592	>200

Water hazard class: WGK 1

Disposal code: VeVA/EWC 130 110

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available for the product described.

